

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims

Claim 1 (currently amended): A method of designing a magnetic field gradient coil assembly using ~~tightly~~ wound inner and outer coils, said method comprising the steps of:

setting or resetting the number of said inner coils and optimizing their positions such that a resulting magnetic field strength falls within a tolerable range of a target magnetic field gradient under shielded conditions;

setting or resetting the number of said outer coils and the number of turns of each outer coil;

calculating Fourier components of an electric current distribution necessary for the outer coils;

optimizing positions of the outer coils to approximate the Fourier components of the current distribution;

calculating magnetic fields leaking from the inner and outer coils, respectively;

calculating magnetic field distortions caused by eddy currents produced by the leaking magnetic fields; and

resetting the number of the outer coils and the number of turns of each outer coil ~~if the magnetic field distortions are outside the tolerable range~~ such that the magnetic field distortions cause by eddy currents fall within a tolerable range.

Claim 2 (currently amended): A method of designing a magnetic field gradient coil assembly as set forth in claim 1, wherein said step of setting or resetting the number of said inner coils and optimizing their positions such that a resulting magnetic field strength falls within a tolerable range of a target magnetic field gradient under shielded conditions uses a ~~Green~~ Green's function.

Claim 3 (currently amended): A method of designing a magnetic field gradient coil assembly as set forth in claim 1, wherein said step of calculating Fourier components of an electric current distribution necessary for the outer coils uses a ~~Green~~ Green's function.

Claim 4 (original): A method of designing a magnetic field gradient coil assembly as set forth in claim 1, wherein said step of optimizing the positions of the outer coils to approximate the Fourier components of the current distribution performs the approximation using a small number of tightly wound coils.

Claim 5 (currently amended): A method of designing a magnetic field gradient coil assembly as set forth in claim 1, wherein said step of calculating magnetic fields leaking from the inner and outer coils, respectively, and said step of calculating magnetic field distortions caused by eddy currents produced by the leaking magnetic fields use a ~~Green~~ Green's function.

Al
Claim 6 (original): A method of designing a magnetic field gradient coil assembly as set forth in claim 1, wherein said step of resetting the number of the outer coils and the number of turns of each outer coil if the magnetic field distortions are outside the tolerable range, said step of calculating Fourier components of an electric current distribution necessary for the outer coils, said step of optimizing the positions of the outer coils to approximate the Fourier components of the current distribution, said step of calculating magnetic fields leaking from the inner and outer coils, respectively, and said step of calculating magnetic field distortions caused by eddy currents produced by the leaking magnetic fields are repeatedly carried out to determine optimum conditions for the outer coils by trial and error.

Claim 7 (currently amended): A magnetic field gradient coil assembly having ~~tightly~~ wound inner and outer coils, said magnetic field gradient coil assembly having been designed by a method comprising the steps of:

setting or resetting the number of said inner coils and the number of turns of each inner coil and optimizing their positions such that a resulting magnetic field strength falls within a tolerable range of a target magnetic field gradient under shielded conditions;

setting the number of said outer coils and the number of turns of each outer coil;

calculating Fourier components of an electric current distribution necessary for the outer coils;

optimizing positions of the outer coils to approximate the Fourier components of the current distribution;

calculating magnetic fields leaking from the inner and outer coils, respectively; and

resetting the number of the outer coils and the number of turns of each outer coil ~~if the magnetic field distortions are outside the tolerable range~~ such that the magnetic field distortions cause by eddy currents fall within a tolerable range.

21
Claim 8 (currently amended): The magnetic field gradient coil assembly of claim 7, wherein said step of setting or resetting the number of said inner coils and optimizing their positions such that a resulting magnetic field strength falls within a tolerable range of a target magnetic field gradient under shielded conditions uses a ~~Green~~ Green's function.

Claim 9 (currently amended): The magnetic field gradient coil assembly of claim 7, wherein said step of calculating Fourier components of an electric current distribution necessary for the outer coils uses a ~~Green~~ Green's function.

Claim 10 (currently amended): The magnetic field gradient coil assembly of claim 7, wherein said step of optimizing the positions of the outer coils to approximate the Fourier components of the current distribution performs the approximation using a small number of ~~tightly~~ wound coils.

Claim 11 (currently amended): The magnetic field gradient coil assembly of claim 7, wherein said step of calculating magnetic fields leaking from the inner and outer coils, respectively, and said step of calculating magnetic field distortions caused by eddy currents produced by the leaking magnetic fields ~~use~~ uses a ~~Green~~ Green's function.

Claim 12 (original): The magnetic field gradient coil assembly of claim 7, wherein said step of resetting the number of the outer coils and the number of turns of each

Application No. 09/732,177
Amendment dated March 8, 2004
Reply to Office Action of December 8, 2003
Attorney Docket No. 116-002064

outer coil if the magnetic field distortions are outside the tolerable range, said step of calculating Fourier components of an electric current distribution necessary for the outer coils, said step of optimizing the positions of the outer coils to approximate the Fourier components of the current distribution, said step of calculating magnetic fields leaking from the inner and outer coils, respectively, and said step of calculating magnetic field distortions caused by eddy currents produced by the leaking magnetic fields are repeatedly carried out to determine optimum conditions for the outer coils by trial and error.

Application No. 09/732,177
Amendment dated March 8, 2004
Reply to Office Action of December 8, 2003
Attorney Docket No. 116-002064

AMENDMENTS TO THE DRAWINGS

The attached sheets of substitute drawings include Figs. 1, 2, 3(a), 3(b), 4(a), 4(b), and 7. Figs. 4(a)-4(b) and 7 were corrected to read "Green's". Figs. 1-4(b) are now designated "Prior Art". Figs. 5(a)-6 are views for used for illustrating embodiments of the present invention, and therefore should not be labeled "Prior Art".

Attachment: Replacement Sheets (8)